

Product Information



DURABOND®

60L™ Latex Additive

Product Description:

DURABOND® 60L™ Latex Additive may be used with Durabond Webpatch® 90 for subfloor preparation. The use of 60L with patches will provide improved resilience, adhesion, and resistance to water and alkali.

Directions for Use:

Read and understand the data sheet completely before beginning installation.

Surface Preparations: All subfloors must be level, firm, dry, smooth, and free of dust, dirt, wax, paint and foreign material. Roughen glossy surfaces or flooring with urethane wear layers. Concrete floors must be free of excessive moisture and alkalinity.

Application:

60L may be used with Webpatch 90 as a replacement to water.

Clean-Up & Storage:

Clean tools with water. To prolong shelf life, the container should be kept closed between spreading cycles and after use. The product should be stored in the original container in a cool, dry place.

Limitations:

- For interior installations only.
- Do not use this product where excessive moisture and alkalinity are present.
- Due to the limitations of plywood as a substrate, it is not intended for wet or exterior installations or applications subject to heavy commercial traffic.

LIMITED WARRANTY

Bostik, Inc. warrants that the product conforms with Bostik's written specifications and is free from manufacturing defects. A PURCHASER'S SOLE REMEDY FOR NONCOMPLIANCE WITH THIS WARRANTY SHALL BE THE REPLACEMENT OF THE PRODUCT OR REFUND OF THE PURCHASE PRICE. Purchasers may address their warranty claims to Bostik, Inc., 211 Boston St., Middleton, MA 01949, Attn: Customer Service or call Bostik at 1-800-7/BOSTIK. TO THE MAXIMUM EXTENT ALLOWED BY LAW, BOSTIK DISCLAIMS ALL OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, AND LIABILITY FOR DIRECT, INCIDENTAL, CONSEQUENTIAL, OR SPECIAL DAMAGES. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitations may not apply to you. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state.

PHYSICAL & CHEMICAL CHARACTERISTICS

Base:	Synthetic Latex and Resin
Vehicle:	Water
Color:	Off White
Density:	8.3 lbs./gal.
Flammability:	Nonflammable
Consistency:	Pourable Liquid
Application:	Pour Spout
Shelf Life:	One Year*

*Stored in original, tightly sealed container

Packaging:

DURABOND 60L is available in 5 gallon and 1 gallon pails. For the name of a distributor nearest you, contact Customer Service at 1-800-7/BOSTIK.



PLANT LOCATIONS

TEMECULA, CA 92590

CONYERS, GA 30207

PAULSBORO, NJ 08066

www.bostik-us.com

December 7, 2009; Supersedes all previously published literature.



211 Boston Street • Middleton, MA 01949 • Customer Service or Technical Service 1-800-7/BOSTIK

www.bostik-us.com