

Product Information



Webpatch™ D-9001 Fast-Setting Latex-Fortified Gypsum Patch

Product Description:

Webpatch™ D-9001 is a fast-setting, latex-fortified gypsum based material designed for interior installation and may be used to patch floors, walls, and other surfaces. Webpatch D-9001 may be used to fill up to 1/2" deep over properly prepared concrete, masonry, cementitious backer board, and structurally sound exterior grade plywood (interior/dry use only). When used properly, this product provides a fast-setting surface that will not check, crack or break up. Webpatch D-9001 may be mixed with DURABOND 60L™ Latex Floor Underlayment Additive instead of water for improved performance.

Product Benefits:

- Repairs minor imperfections in floors and walls
- Latex-fortified
- Compatible with all DURABOND flooring adhesives
- Low installed cost

Performance Characteristics:

- No shrinkage
- Crack resistant
- High strength
- Up to 1/2" depth in one application

Suitable Substrates:

- Properly prepared concrete
- Cementitious backer board
- Masonry
- Drywall
- Structurally sound exterior grade plywood (interior/dry use only)

Surface Preparation:

Surfaces must be structurally sound, clean and free of dust, dirt, paint, soap film, oil, adhesive residue, grease, curing compounds and other foreign material that could inhibit bonding. For best results, material and surface should be above 45°F.

TYPICAL PHYSICAL PROPERTIES

Pot Life:	15-25 minutes
Working Time:	20-30 minutes
Final Set:	25-35 minutes
Cure Time:	Final cure is 28 days*

*Do not allow traffic over floor for 1 hour from installation.

Mixing Instructions:

Add 25 lbs of Webpatch D-9001 to 6 quarts of clean, cool, potable water or 60L Latex Floor Underlayment Additive. Use 1/4 quarts of liquid for 5 lbs of Webpatch D-9001. DO NOT OVER WATER. Do not mix more material than can be used in 10 to 15 minutes. The material may be re-mixed; do not re-temper by adding more liquid. The pot life of the material is dramatically affected by jobsite conditions, the powder/liquid mix ratio, and temperature of the jobsite and materials; cold materials, substrate, jobsite and mixing water will extend the pot life.

Coverage (ft²)*:

Thickness	5 Lbs.	25 Lbs.	30 Lbs.
1/8"	6-8	30-40	36-48
1/6"	15-17	75-85	90-102

*Coverage rates are approximate and actual coverage will vary based on application technique, waste, and/or other jobsite conditions.

Application:

With the flat side of a trowel held at a 45° angle, work patch into surface filling all broken areas, depressions and cracks in the substrate. "Key in" but do not over trowel.

Application over plywood: Please refer to the proper flooring industry and APA standards for plywood subfloor installation and preparation. Clean and rough-sand the plywood. Due to the limitations of plywood as a substrate, it is not intended for use in wet interior, or applications subject to heavy/commercial traffic.



Limitations:

- The use of solvent-based sheet flooring adhesive over Webpatch D-9001 is not recommended; please refer to the applicable DURABOND solvent-free adhesive.
- For areas larger than 4 ft² with a consistent 1/2" depression, the use of a DURABOND self-leveling underlayment product is recommended.
- This product is not designed as a wear surface; an appropriate floor covering must be installed before it is open to normal traffic.
- This product is not recommended as an emboss leveler; use DURABOND Webcrete® 95 mixed with D-L16 or Webcrete 98.

Clean Up, Storage, and Shelf Life:

Wash tools immediately with water. Close container tightly and store unused powder in a cool, dry place. Product has a one-year shelf life.

Packaging:

DURABOND Webpatch is available in 25 lb bags and 5 lb bags (6 x 5lb). For the name of a distributor nearest you, contact Customer Service at 1-800-7/BOSTIK.



PLANT LOCATIONS

TEMECULA, CA 92590

CONYERS, GA 30207

PAULSBORO, NJ 08066

www.bostik-us.com

December 7, 2009; Supersedes all previously published literature.

LIMITED WARRANTY

Bostik, Inc. warrants that the product conforms with Bostik's written specifications and is free from manufacturing defects. A PURCHASER'S SOLE REMEDY FOR NONCOMPLIANCE WITH THIS WARRANTY SHALL BE THE REPLACEMENT OF THE PRODUCT OR REFUND OF THE PURCHASE PRICE. Purchasers may address their warranty claims to Bostik, Inc., 211 Boston St., Middleton, MA 01949, Attn: Customer Service or call Bostik at 1-800-7/BOSTIK. TO THE MAXIMUM EXTENT ALLOWED BY LAW, BOSTIK DISCLAIMS ALL OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, AND LIABILITY FOR DIRECT, INCIDENTAL, CONSEQUENTIAL, OR SPECIAL DAMAGES. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitations may not apply to you. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state.



211 Boston Street • Middleton, MA 01949 • Customer Service or Technical Service 1-800-7/BOSTIK

www.bostik-us.com