



# SuperTak™ Mist

## Product Description

Bostik® SuperTak™ Mist Aerosol Adhesive is especially formulated to exhibit fast, aggressive tack with low soak-in for long lasting bonds on substrates such as foam, cloth, felt, cardboard and paper. SuperTak™ Mist is a transparent, non-staining, non-yellowing, high strength, fine mist aerosol adhesive excellent for a variety of jobs for industry, display, and fixtures. It can be used for temporary or permanent bonds to light weight materials, a variety of substrates, or to itself.

## Features and Benefits

- Spray pattern is a fine particle mist. The valve and tip provides coverage of large areas with a quick uniform coating that offers low soak-in with no staining or wrinkling of lightweight materials.
- Provides similar strength and a one-surface bond comparable to Bostik® SuperTak™ High Performance Aerosol Adhesive, but with the ease of a mist spray.
- Offers high tack bonds for a wide variety of substrates.
- Excellent "green strength"
- Its long open-time and uniform spray pattern provides faster application and less waste.
- Good water resistance
- Elevated temperature resistance
- Does not contain ozone-depleting chemicals, methylene chloride or chlorofluorocarbons
- **Meets or exceeds all Federal and Local VOC limits.**

## Applications

- Bonding carpet and door skins
- Bonding interior carpet and foam material
- Bonding plastics and metals
- Bonding insulation to sheet metal
- Bonding labels and name plates
- Adheres fabric, foam, cardboard, and paper to itself and to metal and some plastics
- Do NOT use SuperTak™ Mist Adhesive to bond unsupported vinyls

## Available Sizes

22.8 FL. OZ. (16.5 OZ. Net Weight) MTO: 52 gal. drum

## Storage and Handling

Shelf Life: One year from ship date  
 Further Information: Extremely flammable. Keep away from sparks, flame or heat. Please refer to MSDS for complete details.

## Typical Physical Properties\* (Not for Specification Use)

Color:	Translucent
Base:	Synthetic resin(s) and styrene butadiene copolymer mixture
Solvent System:	ISO Hexane / Acetone
Solids:	17% ± 1.5%
Heat Resistance:	Constant exposure— 130°F (54°C) Intermittant exposure— 178°F (81°C)
	(Maximum service temperature of cured adhesive)
Physical/Chemical Resistance:	Good resistance to oxidation and moisture
Bonding Time:	1-surface bond— 15 secs.-5 mins. 2-surface bonds— 1-10 mins.
Odor:	Mint-like when wet, none when dry
Spray Pattern:	Valve and tip provides uniform coating, quick coverage of large areas.
Flammability:	Extremely flammable
Cleanup—Suitable Solvents:	Mineral spirits

\* Values given above are not intended to be used in specification preparation.

## Directions for Use

1. Hold the can 6 to 8 inches away from the surface to be sprayed. Depress spray tip (with arrow pointed away from the body) and apply a uniform coating.
2. To clear spray tip, Invert can and spray.
3. For porous substrates, applying two coats in the opposite direction of each other will increase bond strength.
4. For permanent bonding applications, apply a heavy coat to both surfaces, and press substrates together.
5. For temporary bonds, apply a light coat to one surface only, and bond.
6. Read precautions on label before using.
7. Do NOT use adhesive to bond unsupported vinyls.
8. For best results, apply adhesive at temperatures between 50°F (10°C) and 110°F (43°C).

### Bostik, Inc.

211 Boston Street  
 Middleton, MA 01949-2128  
 Customer Service or  
 Technical Service: 800-7/BOSTIK  
 FAX: 978-750-7293  
 www.bostik-us.com

### IMPORTANT NOTICE

All statements, technical information and recommendations set forth herein are based on tests which Bostik believes to be reliable. However, Bostik does not guarantee their accuracy or completeness. The buyer should conduct its own tests of this product before use to determine proper preparation technique and suitability for proposed application. Any sales of this product shall be on terms and conditions set forth on Bostik's order acknowledgment. Bostik, Inc. warrants that the product conforms with Bostik written specifications, and is free from defects. BOSTIK, INC. DISCLAIMS ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE BUYER'S SOLE REMEDY FOR NONCOMPLIANCE WITH THIS WARRANTY SHALL BE FOR THE REPLACEMENT OF THE PRODUCT OR REFUND OF THE BUYER'S PURCHASE PRICE. IN NO CASE WILL BOSTIK, INC. BE LIABLE FOR DIRECT, CONSEQUENTIAL ECONOMIC OR OTHER DAMAGES.